

MB-B	10201	392N(40kg)			58					4.5/8.0+0.02		1.4
CZ-6C	10202	588N(60kg)	55	50	63	176	12	150	10	or	150°	1.5
CZ-8C	10203	784N(80kg)			69					4.5/9.5+0.02		1.7

3. Magnetic Stand With Microadjustment



Model	Order	Work Magnetic Force	Main Body			Main Stem		Assistant Stem		Diameter of Hole	Work Angle	Weight
			H	W	L	Length	Diameter	Length	Diameter			
MB-BV	10301	392N(40kg)			58					4.5/8.0+0.02		1.4
WCZ-6C	10302	588N(60kg)	55	50	63	176	12	150	10	or	150°	1.5
WCZ-8C	10303	784N(80kg)			69					4.58/9.5+0.02		1.7

4. Magnetic Stand With Extra Stem



NO	Model	Order	Work Magnetic Force	Main Body			Main Stem		Assistant Stem		Diameter of Hole	Work Angle	Weight
				H	W	L	Length	Diameter	Length	Diameter			
1	CZ-6CL	10401	588N (60kg)	55	50	63	225	16	180	12	4.5/8.0 +0.02 or 4.58/9.5 +0.02	150°	2.0
2	WCZ-6CL	10402							220				
3	CZ-10DL	10403	980N (100kg)	65	60	100	400	20	380	18		Various Angle	5.0
4	WCZ-10DL	10404							400				
5	CZ-6c-I	10405	588N (60kg)	55	50	63	225	12	190	10		150°	1.5
6	WCZ-6C-I	10406											

Copy Right 2004 YUXIANG Magnetic Materials Ind. Co.,Ltd. All Rights Reserved

Add : F/16, Jinyuan plaza, # 57 South Hubin.Rd, Xiamen, CHINA 361004

Tel : (86)592 2295387 (86)592 2217138 Fax: (86)592 2207122

Email To Us: susana@aaamagnet.net